

Recommended Finishing & Maintenance Instructions

IMPORTANT RETAIN FOR FUTURE REFERENCE: READ CAREFULLY

Protect Your Deck Tiles

Acacia wood, like any solid wood product will react to weather conditions. Although pretreated with hard-wax oil at the factory, the deck tiles may swell or dry out if exposed to snow, rain and sun, resulting in the formation of cracks.

Prior to installation, it is recommended to apply at least two coats of an exterior-grade wood sealant, such as INTERBUILD Hardwax Clear Wood Oil, to the deck tiles, on all surfaces, in order to protect the wood finish and also to protect the wood from weatherization. In addition, for regular deck tile maintenance, it is recommended that an additional coat of an exterior grade wood sealant be applied, as required.

The application of the wood sealant does not affect the durability or function of the deck tiles.

Care, Cleaning & Finish Touch-Ups

In daily use, try to keep the deck tiles clean and dry. If the deck tiles have been sitting outdoors for some time, clean them well before re-application of a wood sealant. The best method is to wash and scrub the tiles with water and a mild cleaner. If necessary, sand the surface with fine sandpaper. Flush and leave to dry thoroughly.

The Interbuild® hardwax wood oil stain finish can be purchased from the same supplier where the deck tiles were purchased to match the original deck tile finish, before a new coat of wood sealant is applied.

Storing

When not using the deck tiles for some time, lift them up so that water can easily run off the surface. When the outdoor season is over, store the deck tiles in a cool place indoors or protect them from the elements to retain their good condition.